





Connettori AMP® Superseal

Disponibili in 3 modelli da 2 a 4 contatti (2, 3, 4). Contatti in ottone stagnato in grado di ospitare fili diametro AWG 22-16 (0,3 - 1,5mm²).

- connettore in nylon 66 caricato vetro;
- guarnizioni e passacavo in silicone garantiscono isolamento IP67
- range di funzionamento da -40°C a +125°C ;
- resistenti a ozono, sali, gasolio, benzina, liquido dei freni, antigelo, lubrificanti.
- corrente massima 14A con cavo AWG16.

Cod.	Cod. AMP AMP ref.	#	
 406204	282104/1	2	50
406240	282105/1	3	50
406218	282106/1	4	50
406220	281934/2		100
406221	282081/1		100
406552	282109/1		100
406552	282109/1		4000 
406552.01	282404/1/4K		100
406552.01	282404/1/4K		4000 




AWG 20-16

AWG 22-20


AMP® Superseal connectors

3 versions available with 2 to 4 contacts (2, 3, 4). Tin-plated brass contacts accommodating wires with AWG 22-16 diameter (0,3 - 1,5 mm²).

- connector in glass loaded 66 nylon;
- silicon seals and cable grip guaranteeing insulation to IP67
- operating range from -40°C to +125°C ;
- resistant to ozone, minerals, diesel, petrol, brake fluid, antifreeze, lubricants.
- maximum current 14A with AWG16 cable.



Cod.	Cod. AMP AMP ref.	#	
 406249	282080/1	2	50
406237	282087/1	3	50
406219	282088/1	4	50
406220	281934/2		100
406221	282081/1		100
406551	282110/1		100
406551	282110/1		4000 

AWG 20-16

Cod.	Cod. AMP AMP ref.	ø (mm)	#	
406205	75553	4	2	50
406238	76319	4	3	50
406238.01		6	3	50
406222	75554	6	4	50



Connettori tipo JST®

Disponibili in 7 modelli da 2 a 10 contatti (2, 3, 4, 6, 7, 8, 10). Contatti in ottone stagnato in grado di ospitare fili diametro AWG 22-18 (0,3 - 1mm²), corrente massima 7A, tensione massima 250V;

Cod.	#	
 406175	2	10
406099	3	10
406049	4	10
406177	6	10
406231	7	10
406173	8	10
406048	10	10

JST®-like connectors

7 versions available with 2 to 10 contacts (2, 3, 4, 6, 7, 8, 10). Tinned brass contacts accommodating wires with AWG 22-18 diameter (0,3 - 1 mm²), maximum current 7A, maximum voltage 250V.

Cod.	#	
406176	2	10
406100	3	10
406051	4	10
406178	6	10
406230	7	10
406174	8	10
406050	10	10
406514		100
406514		3500 

Connettori di potenza AMP®



Connettore bipolare di potenza AMP.

- tensione di esercizio 600 V DC
- corrente continua massima 50 A

AMP® power connectors

AMP bipolar power connector.

- maximum voltage 600 V DC
- maximum current 50 A

Cod.	Cod. AMP AMP ref.	#	
 406279	647845-4	2	1
46279.01	647879/1		10